

Swing Type Check Valve

Applicable Standard:
 Design: BS 1868, ASME B16.34, DIN 3356, EN 10739
 Face to Face : ASME B16.10, BS 2080, ISO 5752, DIN 3202, EN 558
 Flanged Ends: ASME B16.5, ASME B16.47, DIN 2501, EN 1092
 Butt Welding: ASME B16.25, DIN 3239, EN 12627
 Wall Thickness: ASME B16.34
 Testing: API 598, BS EN12266, DIN 3230
 Size: 2"-48", DN50-DN1200
 Pressure Rating: Class 150-2500, PN10-PN420
 Body Material: WCB, LCB, CF8, CF8M, CF3, CF3M, WC6, WC9, C5, CN7M
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel
 Temperature: -180°C to 425°C



Pressure Sealed Bonnet Check Valve

Applicable Standard:
 Design: BS 1868, ASME B16.34, DIN 3356, EN 10739
 Face to Face : ASME B16.10, BS 2080, ISO 5752, DIN 3202, EN 558
 Flanged Ends: ASME B16.5, ASME B16.47, DIN 2501, EN 1092
 Butt Welding: ASME B16.25, DIN 3239, EN 12627
 Wall Thickness: ASME B16.34
 Testing: API 598, BS EN12266, DIN 3230
 Size: 2"-30", DN50-DN750
 Pressure Rating: Class600-Class2500, PN100-PN420
 Body Material: WCB, LCB, CF8, CF8M, CF3, CF3M, WC6, WC9, C5, CN7M
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel
 Temperature: -196 to 600°C



Pressure Sealed Bonnet Check Valve

Applicable Standard:
 Design: BS 1868, ASME B16.34, DIN 3356, EN 10739
 Face to Face : ASME B16.10, BS 2080, ISO 5752, DIN 3202, EN 558
 Flanged Ends: ASME B16.5, ASME B16.47, DIN 2501, EN 1092
 Butt Welding: ASME B16.25, DIN 3239, EN 12627
 Wall Thickness: ASME B16.34
 Testing: API 598, BS EN12266, DIN 3230
 Size: 2"-30", DN50-DN750
 Pressure Rating: Class600-Class2500, PN100-PN420
 Body Material: WCB, LCB, CF8, CF8M, CF3, CF3M, WC6, WC9, C5, CN7M
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel
 Temperature: -196 to 600°C



Forged Steel Bolted Bonnet Check Valve

Applicable Standard:
 Design: API 602, BS 5352, ASME B16.34, EN ISO 15761
 Face to Face : According to manufacturer's standard
 Socket Welding: ASME B16.11
 Threaded: ASME B1.20.1
 Testing: API 598, EN 12266
 Size: 1/4"-4"
 Pressure Rating: Class800-Class1500
 Body Material: A105, LF2, F304, F316, F11, F22, F5
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel
 Temperature: -29°C to 550°C
 Type: Swing Type, Ball Type, Lift Type





Any enquiry, please do not hesitate to contact us at below information.

Email: nor.syamimi@dpservices-ap.com / ridzuanbinali@dpservices-ap.com

Phone Number: 016-885 0251

