

### Cast Steel Bolted Bonnet Gate Valve

Applicable Standard:  
 Design: API 600, BS 1414, ISO 10434, ASME B16.34, DIN 3352, EN 10434  
 Face to Face : ASME B16.10, BS 2080, ISO 5752, DIN 3202, EN 558  
 Flanged Ends: ASME B16.5, ASME B16.47, BS 1560, DIN 2501, EN 1092  
 Butt Welding: ASME B16.25, DIN 3239, EN 12627  
 Wall Thickness: API600, ASME B16.34  
 Testing: API 598, BS EN 12266, ISO 5208, DIN 3230  
 Size: 2"-60", DN50-DN1500  
 Pressure Rating: Class150-Class2500, PN10-PN420  
 Body Material: WCB, LCB, CF8, CF8M, CF3, CF3M, WC6, WC9, C5, CN7M  
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel  
 Temperature: -196°C to 600°C



### Cast Steel Pressure Sealed Bonnet Gate Valve

Applicable Standard:  
 Design: API 600, BS 1414, ISO 10434, ASME B16.34, DIN 3352, EN 10434  
 Face to Face : ASME B16.10, BS 2080, ISO 5752, DIN 3202, EN 558  
 Flanged Ends: ASME B16.5, ASME B16.47, BS 1560, DIN 2501, EN 1092  
 Butt Welding: ASME B16.25, DIN 3239, EN 12627  
 Wall Thickness: API600, ASME B16.34  
 Testing: API 598, BS EN 12266, ISO 5208, DIN 3230  
 Size: 2"-36", DN50-DN900  
 Pressure Rating: Class600-Class2500, PN100-PN420  
 Body Material: WCB, LCB, CF8, CF8M, CF3, CF3M, WC6, WC9, C5, CN7M  
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel  
 Temperature: -196°C to 600°C



### Forged Steel Bolted Bonnet Gate Valve

Applicable Standard:  
 Design: API 602, BS 5352, ASME B16.34, EN ISO 15761  
 Face to Face : According to manufacturer's standard  
 Socket Welding: ASME B16.11  
 Threaded: ASME B1.20.1  
 Testing: API 598, EN 12266  
 Size: 1/4"-4"  
 Pressure Rating: Class 800-1500  
 Body Material: A105, LF2, F304, F316, F11, F22, F5  
 Trim Material: F6a, F304, F304L, F316, F316L, F51, Monel  
 Temperature: -29°C to 550°C



Any enquiry, please do not hesitate to contact us at below information.

Email: [nor.syamimi@dpservices-ap.com](mailto:nor.syamimi@dpservices-ap.com) / [ridzuanbinali@dpservices-ap.com](mailto:ridzuanbinali@dpservices-ap.com)

Phone Number: 016-885 0251

